

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2020

Revision: 08.06.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: B410 RED LUMINA**
- **Article number: B410**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
use as industrial paint
- **Sector of Use**
SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category**
PC9a Coatings and paints, thinners, paint removers
PC9b Fillers, putties, plasters, modelling clay
- **Application of the substance / the mixture** refer to the relevant Technical Data Sheet
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
P.O. Box 7623
Beirut LEBANON
info@hymax.biz
Générale de Peinture, 70 Rue Cortambert 75116 Paris, France
- **Further information obtainable from:** Product Safety Department
- **1.4 Emergency telephone number:** Phone : +33 (0)1 60 86 77 65

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.06.2020

Revision: 08.06.2020

Trade name: B410 RED LUMINA

(Contd. of page 1)

· Hazard pictograms


GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:
n-butyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures
· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

| | | |
|--|---|-----------|
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 | <i>n</i> -butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336 | >50-≤100% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32 | xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | >2.5-≤10% |

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.06.2020

Revision: 08.06.2020

Trade name: B410 RED LUMINA

(Contd. of page 2)

| | | |
|---|--|-----------|
| CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27 | Solvent naphtha (petroleum), light arom. ⚠ Acute Tox. 4, H332; STOT SE 3, H335 | >2.5-≤10% |
| CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 05-2116413226-56 | 2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 | >2.5-≤10% |
| CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36 | 2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 | ≤2.5% |
| CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35 | ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332 | ≤2.5% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

GB

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2020

Revision: 08.06.2020

Trade name: B410 RED LUMINA

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

| | |
|-----|---|
| WEL | Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm |
|-----|---|

1330-20-7 xylene

| | |
|-----|--|
| WEL | Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm |
| | Sk; BMGV |

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.06.2020

Revision: 08.06.2020

Trade name: B410 RED LUMINA

(Contd. of page 4)

108-65-6 2-methoxy-1-methylethyl acetate

| | |
|-----|--|
| WEL | Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk |
|-----|--|

111-76-2 2-butoxyethanol

| | |
|-----|---|
| WEL | Short-term value: 246 mg/m ³ , 50 ppm Long-term value: 123 mg/m ³ , 25 ppm Sk, BMGV |
|-----|---|

100-41-4 ethylbenzene

| | |
|-----|---|
| WEL | Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk |
|-----|---|

· Ingredients with biological limit values:
1330-20-7 xylene

| | |
|------|--|
| BMGV | 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid |
|------|--|

111-76-2 2-butoxyethanol

| | |
|------|---|
| BMGV | 240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid |
|------|---|

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2020

Revision: 08.06.2020

Trade name: B410 RED LUMINA

(Contd. of page 5)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

| | |
|-------------------------|-----------------|
| Form: | Liquid |
| Colour: | Red |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

| | |
|---|---------------|
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | 120 °C |

· **Flash point:** 27 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 315 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

| | |
|---------------|-----------|
| Lower: | 1.2 Vol % |
| Upper: | 7.5 Vol % |

· **Vapour pressure at 20 °C:** 10.7 hPa

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.06.2020

Revision: 08.06.2020

Trade name: B410 RED LUMINA

(Contd. of page 6)

| | |
|--|--|
| · Density at 20 °C: | 0.953 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 74.8 % |
| VOC (EC) | 712.5 g/l |
| Solids content: | 27.8 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

1330-20-7 xylene

| | | |
|--------|------|----------------------|
| Oral | LD50 | 4,300 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

64742-95-6 Solvent naphtha (petroleum), light arom.

| | | |
|--------|------|--------------------|
| Oral | LD50 | >6,800 mg/kg (rat) |
| Dermal | LD50 | >3,400 mg/kg (rab) |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.06.2020

Revision: 08.06.2020

Trade name: B410 RED LUMINA

(Contd. of page 7)

| | | |
|------------|----------|------------------|
| Inhalative | LC50/4 h | >10.2 mg/l (rat) |
|------------|----------|------------------|

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB
(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31


Printing date 15.06.2020

Revision: 08.06.2020

Trade name: B410 RED LUMINA

(Contd. of page 8)

SECTION 14: Transport information

| | |
|--|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | <p>UN1263</p> |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA | <p>1263 PAINT PAINT</p> |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA <div style="text-align: center; margin: 10px 0;">  </div> <ul style="list-style-type: none"> · Class · Label | <p>3 Flammable liquids. 3</p> |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | <p>III</p> |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | <p>No</p> |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · EMS Number: · Stowage Category | <p>Warning: Flammable liquids. F-E, S-E A</p> |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | <p>Not applicable.</p> |
| <ul style="list-style-type: none"> · Transport/Additional information: | |
| <ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) | <p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p> |
| <ul style="list-style-type: none"> · Transport category · Tunnel restriction code | <p>3 D/E</p> |
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | <p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p> |

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2020

Revision: 08.06.2020

Trade name: B410 RED LUMINA

(Contd. of page 9)

· **UN "Model Regulation":** UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- **Department issuing SDS:** Product safety department
- **Contact:** N/A
- **Abbreviations and acronyms:**
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.06.2020

Revision: 08.06.2020

Trade name: B410 RED LUMINA

(Contd. of page 10)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity - dermal – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

GB