



Printing date 25.09.2019 Revision: 06.05.2019

### SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: T970 METALLIC BASE MEDIUM FINE
- · Article number: T970
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against use as industrial paint
- · Sector of Use

SU3 Industrial Uses: Uses of substances such as or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC9a Coatings and paints, thinners, paint removers

PC9b Fillers, putties, plasters, modelling clay

- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

P.O. Box 7623

Beirut LEBANON

info@hymax.biz

Générale de Peinture, 70 Rue Cortambert 75116 Paris, France

Tel:+33(0)175293559

- · Further information obtainable from: Product Safety Department
- 1.4 Emergency telephone number: +33 (0)6 07 87 13 41

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.

(Contd. on page 2)



Page 2/12

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Revision: 06.05.2019

Trade name: T970 METALLIC BASE MEDIUM FINE

(Contd. of page 1)



Skin Irrit. 2 H315 Causes skin irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrodesulfurized heavy

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · Additional information:

Contains methyl methacrylate, 2,3-epoxypropyl neodecanoate, 2-hydroxyethyl methacrylate. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3)



Page 3/12

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Revision: 06.05.2019

Trade name: T970 METALLIC BASE MEDIUM FINE

· vPvB: Not applicable.

(Contd. of page 2)

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate  This is a second of the control of	>10-≤25%	
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119486136-34 05-2116602925-45 01-2119488216-32	xylene  Tripology  Tri	>10- <i>≤</i> 25%	
CAS: 7429-90-5 EINECS: 231-072-3	aluminium powder (pyrophoric)  Pyr. Sol. 1, H250; Water-react. 2, H261	>2.5- <i>≤</i> 10%	
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35 05-2116598517-27	Solvent naphtha (petroleum), light arom.  • Acute Tox. 4, H332; STOT SE 3, H335	≤2.5%	
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy Flam. Liq. 3, H226;  STOT RE 1, H372; Asp. Tox. 1, H304	<i>≤</i> 2.5%	
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate  Tlam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<i>≤</i> 2.5%	
CAS: 26761-45-5 EINECS: 247-979-2 Reg.nr.: 01-2119431597-33	2,3-epoxypropyl neodecanoate ♠ Acute Tox. 3, H331; ♠ Aquatic Chronic 2, H411; ♠ Skin Irrit. 2, H315; Skin Sens. 1, H317	<i>≤</i> 2.5%	
CAS: 868-77-9 EINECS: 212-782-2 Reg.nr.: 01-2119490169-29	2-hydroxyethyl methacrylate  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	<i>≤</i> 2.5%	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

GB



Page 4/12

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Revision: 06.05.2019

Trade name: T970 METALLIC BASE MEDIUM FINE

(Contd. of page 3)

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

#### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full let
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)



Page 5/12

according to 1907/2006/EC, Article 31

Printing date 25.09.2019

Revision: 06.05.2019

Trade name: T970 METALLIC BASE MEDIUM FINE

See Section 13 for disposal information.

(Contd. of page 4)

#### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

	· Ingredients	with limit	values	tnat re	equire n	nonitoring	at tne	workplace:
--	---------------	------------	--------	---------	----------	------------	--------	------------

#### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

#### 1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

#### 80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

#### · Ingredients with biological limit values:

#### 1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

(Contd. on page 6)



Page 6/12

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Revision: 06.05.2019

Trade name: T970 METALLIC BASE MEDIUM FINE

(Contd. of page 5)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

GE





Printing date 25.09.2019 Revision: 06.05.2019

Trade name: T970 METALLIC BASE MEDIUM FINE

(Contd. of page 6)

SECTION 9: Physical and chemic	car properties
9.1 Information on basic physical and o	hemical properties
· General Information	
· Appearance:	
Form:	Liquid
Colour:	Silver grey
· Odour:	Characteristic
Odour threshold:	Not determined.
· pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	: 124 °C
· Flash point:	25 ℃
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosi air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.998 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	42.1 %





Printing date 25.09.2019 Revision: 06.05.2019

Trade name: T970 METALLIC BASE MEDIUM FINE

(Contd. of page 7)

VOC (EC)	420.1 g/l	
Solids content:  9.2 Other information	57.3 % No further relevant information available.	

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:			
1330-20-7	1330-20-7 xylene			
Oral	LD50	4,300 mg/kg (rat)		
Dermal	LD50	2,000 mg/kg (rabbit)		
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.			
Oral	LD50	>6,800 mg/kg (rat)		
Dermal	LD50	>3,400 mg/kg (rab)		
	LC50/4 h	>10.2 mg/l (rat)		

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

May cause damage to the central nervous system through prolonged or repeated exposure.

(Contd. on page 9)



Page 9/12

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Revision: 06.05.2019

Trade name: T970 METALLIC BASE MEDIUM FINE

(Contd. of page 8)

· Aspiration hazard Based on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT	

(Contd. on page 10)





Printing date 25.09.2019 Revision: 06.05.2019

Trade name: T970 METALLIC BASE MEDIUM FINE

	(Contd. of page
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user · EMS Number:	Warning: Flammable liquids.
· EMS Number: · Stowage Category	F-E, <u>S-E</u> A
· 14.7 Transport in bulk according to Ann	nex II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1  Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per nitrer packaging: 30 mi Maximum net quantity per outer packaging: 1000 n
Transport category	3
· Tunnel restriction code	D/E
· IMDG	
<ul> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E1
· LACEPIEU Quantities (EW)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 n
· UN "Model Regulation":	UN 1263 PAINT, 3, III

GB



Page 11/12

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Revision: 06.05.2019

Trade name: T970 METALLIC BASE MEDIUM FINE

(Contd. of page 10)

#### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H250 Catches fire spontaneously if exposed to air.

H261 In contact with water releases flammable gases.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eve irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

· Contact: N/A

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)



Page 12/12

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.09.2019 Revision: 06.05.2019

#### Trade name: T970 METALLIC BASE MEDIUM FINE

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Pyr. Sol. 1: Pyrophoric solids – Category 1

Water-react. 2: Substances and mixtures which in contact with water emit flammable gases - Category 2

Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2