



N07Y- Polyester Putty Beige

Description:


This great metal filler is a multi-purpose putty with an extremely smooth application. It can be applied vertically without running and exhibits high resistance to almost all solvents. It is characterized by very easy sanding and the advantage of withstanding temperatures of 100°C without any distortions.

Suitable Substrates:

- Iron, steel plate, glass fiber reinforced plastic
- Original paints or aged topcoat finishes

Surface preparation:

- Clean well the surface to be treated with S241 Genclean. Make sure it is dry and free from Silicone, wax, grease and any extraneous material.
- On basecoats or enamel top coats, sand and clean the surface before applying the filler.



1 – 3% Hymax hardener
Potlife 3 - 5 min at 20°C



Application with putty knife



< 30 min at 20°C



4 – 5 min at 1 m.



Initial Sanding with P60 – P120 roughing-out
Final Sanding with P180 – P220 finishing



N07Y- Polyester Putty Beige

Composition: Unsaturated polyester resin and mineral charges

Specific weight: 1.88 ± 0.1

Available colors: Beige, Grey

VOC (2004/42/EC): 2004/42/IIB (b) (250)250. The EU limit value for this product (product category IIB.b) in ready to use form is max 250g/ltr. The VOC content of this product in ready for use form is max. 250 g/l.

SDS: See the safety data sheet